

Weaver Recommended Torque Specs

Item ID	Item Name	Torque Specs
Axial Load to Torque of Fastener		
6-48 @ 15 in lbs = 555 lbs 8-40 @ 18 in lbs = 562 lbs 6-48 @ 30 in lbs = 1111 lbs 6-48 @ 35 in lbs = 1296 lbs		
10-32 @ 35 in lbs = 945 lbs 10-32 @ 48 in lbs = 1297 10-32 @ 65 in lbs 1756 lbs		

48320	AR 15 SNGL RAIL HANDLE MT	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48321	AR 15 SNGL RAIL FLAT TOP MT	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48370	THUMBNUT 1" PIC ADPT SCOPE	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48372	THUMBNUT TACTICAL MOUNTS RISER RAIL	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48373	THUMBNUT 30MM PIC ADPT SCOPE	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48375	THUMBNUT TACTICAL MOUNTS SPR 30MM	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48376	THUMBNUT TACTICAL MOUNTS SPR 1"	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
99465	EXTENDED MULTI SLOT BASE SAVAGE 110 LA 8-40	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
99466	EXTENDED MULTI SLOT BASE SAVAGE 10 SA 8-40	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
99467	EXTENDED MULT SLOT BASE MOSSBERG MVP	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
99468	EXTENDED MULTI SLOT BASE RUGER AMERICAN LA	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
99469	EXTENDED MULTI SLOT BASE RUGER AMERICAN SA	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
99470	EXTENDED MULTI SLOT BASE TIKKA T3X LA	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
99472	EXTENDED MULTI SLOT BASE BROWNING AB3 LA	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
99473	EXTENDED MULTI SLOT BASE BROWNING AB3 SA	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
99474	EXTENDED MULTI SLOT BASE MOSSBERG PATRIOT LA	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
99475	EXTENDED MULTI SLOT BASE MOSSBERG PATRIOT SA	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs

Weaver Recommended Torque Specs

Item ID	Item Name	Torque Specs
Axial Load to Torque of Fastener 6-48 @ 15 in lbs = 555 lbs 8-40 @ 18 in lbs = 562 lbs 6-48 @ 30 in lbs = 1111 lbs 6-48 @ 35 in lbs = 1296 lbs 10-32 @ 35 in lbs = 945 lbs 10-32 @ 48 in lbs = 1297 10-32 @ 65 in lbs 1756 lbs		
99476	EXTENDED MULTI SLOT BASE WINCHESTER XPR LA	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
99477	EXTENDED MULTI SLOT BASE WINCHESTER XPR SA	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
99480	EXTENDED MULTI SLOT BASE WINCHESTER MODEL 70 LA	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
99481	EXTENDED MULTI SLOT BASE WINCHESTER MODEL 70 SA	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
99487	EXTENDED MULTI SLOT BASE SAVAGE AXIS	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
99488	EXTENDED MULTI SLOT BASE SAVAGE AXIS 20 MOA	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
99489	EXTENDED MULTI SLOT BASE SAVAGE 110, 111, 112, 114, 116 LA	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
99490	EXTENDED MULTI SLOT BASE SAVAGE 110, 111, 112, 114, 116 LA 2	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
99491	EXTENDED MULTI SLOT BASE SAVAGE 10, 11, 12, 14, 16 SA (6-48)	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
99492	EXTENDED MULTI SLOT BASE SAVAGE 10, 11, 12, 14, 16 SA 20 MOA	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
99497	Savage Target Tact LA 20MOA	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
99498	Savage Target Tact SA 20MOA	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
99501	EXTENDED MULTI SLOT BASE REMINGTON 700 LA	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
99502	EXTENDED MULTI SLOT BASE REMINGTON 700 LA 20 MOA	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
99503	EXTENDED MULTI SLOT BASE REMINGTON 700 SA	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
99504	EXTENDED MULTI SLOT BASE REMINGTON 700 SA 20 MOA	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
99505	EXTENDED MULTI SLOT BASE REMINGTON 783 LA	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
99506	EXTENDED MULTI SLOT BASE REMINGTON 783 SA	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs

Weaver Recommended Torque Specs

Item ID	Item Name	Torque Specs
Axial Load to Torque of Fastener		
6-48 @ 15 in lbs = 555 lbs 8-40 @ 18 in lbs = 562 lbs 6-48 @ 30 in lbs = 1111 lbs 6-48 @ 35 in lbs = 1296 lbs		
10-32 @ 35 in lbs = 945 lbs 10-32 @ 48 in lbs = 1297 10-32 @ 65 in lbs 1756 lbs		

99658	PICATINNY RISER SET	Cap: 15 in lbs Crossbolt: 35 in lbs
99671	ADAPTOR. OFFSET RAIL	Cap: 15 in lbs Crossbolt: 35 in lbs
99673	PICATINNY RISER RAIL	Cap: 15 in lbs Crossbolt: 35 in lbs
99674	MOUNT, SPR 30MM OPTICS	Cap: 15 in lbs Crossbolt: 35 in lbs
99675	RAIL, AR15 20MOA FLAT TOP RISER	Cap: 15 in lbs Crossbolt: 35 in lbs

48001	BASE,TOP MT,401S	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48002	BASE,TOP MT,61S	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48003	BASE,TOP MT,47S	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48004	BASE,TOP MT,46S	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48005	BASE,TOP MT,36S	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48006	BASE,TOP MT,35S	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48011	BASE,TOP,11	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48012	BASE,TOP MT,12	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48013	BASE,TOP MT,13	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48014	BASE,TOP MT,14	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48015	BASE,TOP MT,15	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48016	BASE,TOP MT,16	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48018	BASE,TOP MT,18	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48019	BASE,TOP MT,19	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48020	BASE,TOP MT,20A	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs

Weaver Recommended Torque Specs

Item ID	Item Name	Torque Specs
Axial Load to Torque of Fastener 6-48 @ 15 in lbs = 555 lbs 8-40 @ 18 in lbs = 562 lbs 6-48 @ 30 in lbs = 1111 lbs 6-48 @ 35 in lbs = 1296 lbs 10-32 @ 35 in lbs = 945 lbs 10-32 @ 48 in lbs = 1297 10-32 @ 65 in lbs 1756 lbs		
48023	BASE,TOP MT,23	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48024	BASE,TOP MT,24	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48025	BASE,TOP MT,25	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48028	BASE,TOP MT,28	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48029	BASE,TOP MT,29	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48030	BASE,TOP MT,30	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48035	BASE,TOP MT,35	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48036	BASE,TOP MT,36	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48040	BASE,TOP MT,40A	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48042	BASE,TOP MT,42	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48043	BASE,TOP MT,43	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48045	BASE,TOP MT,45	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48046	BASE,TOP MT,46	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48047	BASE,TOP MT,47	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48053	BASE,TOP MT,53	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48054	BASE,TOP MT,54	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48055	BASE,TOP MT,55	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48059	BASE,TOP MT,59	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs

Weaver Recommended Torque Specs

Item ID	Item Name	Torque Specs
Axial Load to Torque of Fastener 6-48 @ 15 in lbs = 555 lbs 8-40 @ 18 in lbs = 562 lbs 6-48 @ 30 in lbs = 1111 lbs 6-48 @ 35 in lbs = 1296 lbs 10-32 @ 35 in lbs = 945 lbs 10-32 @ 48 in lbs = 1297 10-32 @ 65 in lbs 1756 lbs		
48060	BASE,TOP MT,61A	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48061	BASE,TOP MT,61	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48062	BASE,TOP MT,62	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48064	BASE,TOP MT,60A	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48067	BASE,TOP MT,67	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48068	BASE,TOP MT,68	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48069	BASE,TOP MT,63B	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48070	BASE,TOP MT,70	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48071	BASE,TOP MT,71	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48074	BASE,TOP MT,74	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48075	BASE,TOP MT,75	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48076	BASE,TOP MT,76	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48080	BASE,TOP MT,80	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48082	BASE,TOP MT,82	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48085	BASE,TOP MT,85	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48086	BASE,TOP MT,86	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48087	BASE,TOP MT,87	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48088	BASE,TOP MT,88	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs

Weaver Recommended Torque Specs

Item ID	Item Name	Torque Specs
Axial Load to Torque of Fastener 6-48 @ 15 in lbs = 555 lbs 8-40 @ 18 in lbs = 562 lbs 6-48 @ 30 in lbs = 1111 lbs 6-48 @ 35 in lbs = 1296 lbs 10-32 @ 35 in lbs = 945 lbs 10-32 @ 48 in lbs = 1297 10-32 @ 65 in lbs 1756 lbs		
48090	BASE,TOP MT,90	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48092	BASE,TOP MT,92A	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48093	BASE,TOP MT,93	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48094	BASE,TOP MT,94	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48095	BASE,TOP MT,95	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48096	BASE,TOP MT,96	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48097	BASE,TOP MT,97	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48098	BASE,TOP MT,98	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48099	BASE,TOP MT,99	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48107	BASE,TOP MT,403A	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48108	BASE,TOP MT,402	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48109	BASE,TOP MT,401	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48110	BASE,406 THUNDERHAWK	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48113	BASE, HR PARDNER PUMP	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48420	BASE, TOP MT 653M	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48421	BASE, TOP MT 654M	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48425	BASE,TOP MT,413	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48426	BASE,TOP MT,414M	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs

Weaver Recommended Torque Specs

Item ID	Item Name	Torque Specs
Axial Load to Torque of Fastener 6-48 @ 15 in lbs = 555 lbs 8-40 @ 18 in lbs = 562 lbs 6-48 @ 30 in lbs = 1111 lbs 6-48 @ 35 in lbs = 1296 lbs 10-32 @ 35 in lbs = 945 lbs 10-32 @ 48 in lbs = 1297 10-32 @ 65 in lbs 1756 lbs		
48428	BASE,TOP MT,40AM	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48429	BASE,TOP MT,402M	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48430	BASE,TOP MT,402S	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48432	BASE,TOP MT,415M	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48434	BASE,TOP MT,416M	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48435	BASE,TOP MT,418M	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48437	BASE,TOP MT,419M	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48438	BASE #420M	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48440	BASE 417M	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48442	BASE #413M	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48443	BASE, TOP MT 423M MATTE	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48444	BASE, TOP MT 421M	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48447	BASE, TOP MOUNT, 63BS	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48453	BASE, TOP MT 418S SILVER	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48454	BASE,TOP MOUNT #429M	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48455	BASE, TOP MT, 430M	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48456	BASE,BRWNG BAR #432M	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48500	BASE,TOP MT,35M	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs

Weaver Recommended Torque Specs

Item ID	Item Name	Torque Specs
Axial Load to Torque of Fastener		
6-48 @ 15 in lbs = 555 lbs 8-40 @ 18 in lbs = 562 lbs 6-48 @ 30 in lbs = 1111 lbs 6-48 @ 35 in lbs = 1296 lbs		
10-32 @ 35 in lbs = 945 lbs 10-32 @ 48 in lbs = 1297 10-32 @ 65 in lbs 1756 lbs		

48501	BASE,TOP MT,36M	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48502	BASE,TOP MT,46M	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48503	BASE,TOP MT,47M	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48504	BASE,TOP MT,61M	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48506	BASE,TOP MT #93A	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48513	BASE, TOP MT,410	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48632	BASE,TOP MT,411	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs

48460	BASE PAIR, REM 700 MATTE	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48461	BASE PAIR, REM 700 SILVER	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48462	BASE PAIR, BROWNING A-BOLT MATTE	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48464	BASE PAIR, MAUSER 98 MATTE	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48465	BASE PAIR, SAV 110 (PRE 03) MATTE	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48466	BASE PAIR, SAVE 110 (ACCU) MATTE	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48468	BASE PAIR, WIN 70 MATTE	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48470	BASE PAIR, BROWNING BAR MATTE	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48471	BASE PAIR, MARLIN 336 MATTE	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48472	BASE PAIR, REM 7400 MATTE	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48473	BASE PAIR, MOSS 500/835 MATTE	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs

Weaver Recommended Torque Specs

Item ID	Item Name	Torque Specs
Axial Load to Torque of Fastener 6-48 @ 15 in lbs = 555 lbs 8-40 @ 18 in lbs = 562 lbs 6-48 @ 30 in lbs = 1111 lbs 6-48 @ 35 in lbs = 1296 lbs 10-32 @ 35 in lbs = 945 lbs 10-32 @ 48 in lbs = 1297 10-32 @ 65 in lbs 1756 lbs		
48474	BASE PAIR, RUGER 10/22 MATTE	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48475	BASE PAIR, WIN 94 MATTE	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48476	BASE PAIR, TIKKA T3	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48477	BASE PAIR, REMINGTON 783	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48478	BASE PAIR, SAVAGE A17/A22 MAG	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48480	BASE PAIR, SAVAGE B-MAG	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48481	BASE PAIR, BROWNING AB3	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48482	BASE PAIR, WINCHESTER XPR	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48483	BASE PAIR, MOSSBERGE PATRIOT	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48484	BASE PAIR REM 700(WM)MATTE	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48489	BASE PAIR SAVAGE 110, 8-40	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48488	BASE PAIR SAVAGE 110	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48492	BASE PAIR, MARLIN 336	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48493	BASE BROWNING X-BOLT MATTE	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48494	BASE PAIR, RUGER 10/22 MATTE(WM)	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48495	BASE BROWNING X-BOLT SILVER	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48009	BASE,TOP MT,TO9S	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48201	BASE,TIP OFF,TO9	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs

Weaver Recommended Torque Specs

Item ID	Item Name	Torque Specs
Axial Load to Torque of Fastener		
6-48 @ 15 in lbs = 555 lbs 8-40 @ 18 in lbs = 562 lbs 6-48 @ 30 in lbs = 1111 lbs 6-48 @ 35 in lbs = 1296 lbs		
10-32 @ 35 in lbs = 945 lbs 10-32 @ 48 in lbs = 1297 10-32 @ 65 in lbs 1756 lbs		

48203	TIP-OFF BASE TO-1	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48459	BASE PAIR T-22	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48505	BASE,TIP OFF,TO9M	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48511	BASE,TIP OFF,TO11,RGR 96/22	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs

48300	BASE, MULTI SLOT CVA OPTIMA, ACCURA, WOLF	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48302	BASE, MULTI SLOT 600 SAVAGE RASCAL W/CUT OUT	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48304	BASE, MULTI SLOT 601 SAV MK I, II, & 93 W/CUT OUT E-REC	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48305	BASE, MULTI SLOT 602 SAVAGE BMAG	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48306	BASE, MULTI SLOT 603 SAVAGE MODEL 64	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48307	BASE, MULTI SLOT 604 SAVAGE A22	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48308	BASE, MULTI SLOT 605 SAVAGE A17 & A22MAG	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48309	BASE, MULTI SLOT 606 SAVAGE B SERIES	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48310	BASE, MULTI SLOT 607 REMINGTON 783 SA	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48311	BASE, MULTI SLOT 608 REMINGTON 783 LA	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48312	BASE, MULTI SLOT 609 RUGER AMERICAN SA	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48313	BASE, MULTI SLOT 610 RUGER AMERICAN LA	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48314	BASE, MULTI SLOT 611 BROWNING AB3 SA	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48315	BASE, MULTI SLOT 612 BROWNING AB3 LA	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs

Weaver Recommended Torque Specs

Item ID	Item Name	Torque Specs
Axial Load to Torque of Fastener 6-48 @ 15 in lbs = 555 lbs 8-40 @ 18 in lbs = 562 lbs 6-48 @ 30 in lbs = 1111 lbs 6-48 @ 35 in lbs = 1296 lbs 10-32 @ 35 in lbs = 945 lbs 10-32 @ 48 in lbs = 1297 10-32 @ 65 in lbs 1756 lbs		
48316	BASE, MULTI SLOT 613 WINCHESTER XPR SA	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48317	BASE, MULTI SLOT 614 WINCHESTER XPR LA	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48318	BASE, MULTI SLOT 615 MOSSBURG Patriot SA	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48319	BASE, MULTI SLOT 616 MOSSBURG Patriot LA	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48329	BASE,MULTISLOT 413T SAVAGE 110LA	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48330	BASE,MULTISLOT 97T REMINGTON 700SA	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48333	BASE,MULTISLOT 417T MOSSBERG 500	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48334	BASE,MULTISLOT 98T REMINGTON 700 LA	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48335	BASE,MULTISLOT 430T RUGER 10/22	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48336	BASE,MULTISLOT 414T REMINGTON 597	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48337	BASE,MULTISLOT 416T WINCHESTER 1300	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48338	BASE,MULTISLOT 431T SAV ACCUTRGR SA	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48339	BASE,MULTISLOT 93AT BENELLI	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48343	BASE,MULTISLOT 618, SAVAGE 10 SA, 8-40	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48344	BASE,MULTISLOT 619, SAVAGE 110 LA, 8-40	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48345	BASE, MULTI-SLOT REM 870 1PC	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48347	Base Multi Slot Savage Axis	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48340	Shotgun Mount Remington 870	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs Cap: 15 in lbs Crossbolt: 35 in lbs

Weaver Recommended Torque Specs

Item ID	Item Name	Torque Specs
Axial Load to Torque of Fastener 6-48 @ 15 in lbs = 555 lbs 8-40 @ 18 in lbs = 562 lbs 6-48 @ 30 in lbs = 1111 lbs 6-48 @ 35 in lbs = 1296 lbs 10-32 @ 35 in lbs = 945 lbs 10-32 @ 48 in lbs = 1297 10-32 @ 65 in lbs 1756 lbs		
48341	Shotgun Mount Mossberg 500	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs Cap: 15 in lbs Crossbolt: 35 in lbs
48521	MT SYSTEM TRADITIONS/CVA	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs Cap: 15 in lbs Crossbolt: 35 in lbs
48544	R&B SET,1PC CVA/TRADITIONS HIGH	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs Cap: 15 in lbs Crossbolt: 35 in lbs
48401	BASE,SIDE MT,#1	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48402	BASE,SIDE MT,#2	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48412	BASE,SIDE MT,#3B	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
49340	SIDE MT, 1" LONG HIGH BRACKET	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
49350	SIDE MT, 1" HIGH BRACKET	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48496	SMITH X-FRAME HANDGUN MOUNT	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs Cap: 15 in lbs Crossbolt: 35 in lbs
99679	1" Fixed MSR Mount	Cap: 25 in lbs Crossbolt: 45 in lbs
99680	30mm Fixed MSR Mount	Cap: 25 in lbs Crossbolt: 45 in lbs
99681	34MM FIXED MSR MOUNT	Cap: 25 in lbs Crossbolt: 45 in lbs
48224	BASE, GRAND SLAM, S35	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48225	BASE, GRAND SLAM, S36	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48226	BASE, GRAND SLAM, S45	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48227	BASE, GRAND SLAM, S46	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48234	BASE, GRAND SLAM, S61	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs

Weaver Recommended Torque Specs

Item ID	Item Name	Torque Specs
Axial Load to Torque of Fastener 6-48 @ 15 in lbs = 555 lbs 8-40 @ 18 in lbs = 562 lbs 6-48 @ 30 in lbs = 1111 lbs 6-48 @ 35 in lbs = 1296 lbs 10-32 @ 35 in lbs = 945 lbs 10-32 @ 48 in lbs = 1297 10-32 @ 65 in lbs 1756 lbs		
48247	BASE, GRAND SLAM, S402	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48260	BASE, GRAND SLAM, S670 (SAVAGE 10/110 8-40)	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48261	BASE, GRAND SLAM, S671 (SAVAGE 10/110 8-40)	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
48282	BASE, GRAND SLAM, S466	6-48 Screws: 15 in lbs 8-40 Screws: 18 in lbs
49213	RING WVR STEEL 22 CAL HI MATTE	Cap: 15 in lbs Crossbolt: 35 in lbs
49217	RING, 1"22 MED MATTE	Cap: 15 in lbs Crossbolt: 35 in lbs
49219	RING, 1"22 X-HI MATTE	Cap: 15 in lbs Crossbolt: 35 in lbs
49325	RING WVR LEVER LOK 1"MED MATTE	Cap: 15 in lbs Crossbolt: 35 in lbs
49326	RING WVR LEVER LOK 1"HI MATTE	Cap: 15 in lbs Crossbolt: 35 in lbs
49327	RING WVR LEVER LOK 1"EX-HI MATTE	Cap: 15 in lbs Crossbolt: 35 in lbs
49335	RING WVR LEVER LOK 30MM HI MATTE	Cap: 15 in lbs Crossbolt: 35 in lbs
49302	RING 1" WVR STEEL MED BLACK	Cap: 15 in lbs Crossbolt: 35 in lbs
49303	RING 1" WVR STEEL MED MATTE	Cap: 15 in lbs Crossbolt: 35 in lbs
49304	RING 1" WVR STEEL HIGH BLACK	Cap: 15 in lbs Crossbolt: 35 in lbs
49305	RING 1" WVR STEEL HIGH MATTE	Cap: 15 in lbs Crossbolt: 35 in lbs
49306	RING 1" WVR STEEL X-HIGH BLACK	Cap: 15 in lbs Crossbolt: 35 in lbs
49302	RING 1" WVR STEEL MED BLACK	Cap: 20 in lbs Crossbolt: 30 in lbs
49303	RING 1" WVR STEEL MED MATTE (PAIR)	Cap: 20 in lbs Crossbolt: 30 in lbs
49304	RING 1" WVR STEEL HIGH BLACK	Cap: 20 in lbs Crossbolt: 30 in lbs
49305	RING 1" WVR STEEL HIGH MATTE	Cap: 20 in lbs Crossbolt: 30 in lbs
49306	RING 1" WVR STEEL X-HIGH BLACK	Cap: 20 in lbs Crossbolt: 30 in lbs
49307	RING 1" WVR STEEL X-HIGH MATTE	Cap: 20 in lbs Crossbolt: 30 in lbs
49309	RING 30 MM WVR STEEL HIGH MATT	Cap: 20 in lbs Crossbolt: 30 in lbs
49318	RING WVR STEEL W/A 1"MED MATTE	Cap: 20 in lbs Crossbolt: 30 in lbs
49319	RING WVR STEEL W/A 1"HI MATTE	Cap: 20 in lbs Crossbolt: 30 in lbs
49320	RING WVR STEEL W/A 1"X-HI MATTE	Cap: 20 in lbs Crossbolt: 30 in lbs

Weaver Recommended Torque Specs

Item ID	Item Name	Torque Specs
Axial Load to Torque of Fastener 6-48 @ 15 in lbs = 555 lbs 8-40 @ 18 in lbs = 562 lbs 6-48 @ 30 in lbs = 1111 lbs 6-48 @ 35 in lbs = 1296 lbs 10-32 @ 35 in lbs = 945 lbs 10-32 @ 48 in lbs = 1297 10-32 @ 65 in lbs 1756 lbs		
49321	RING WVR STEEL MED SILVER	Cap: 20 in lbs Crossbolt: 30 in lbs
49322	RING WVR STEEL HIGH SILVER	Cap: 20 in lbs Crossbolt: 30 in lbs
49046	RING, QUAD LOCK 1" MED, MATTE	Cap: 15 in lbs Crossbolt: 30 in lbs
49047	RING, QUAD LOCK 1" HIGH, MATTE	Cap: 15 in lbs Crossbolt: 30 in lbs
49048	RING,QUAD LOK 1"HIGH, EXT MAT	Cap: 15 in lbs Crossbolt: 30 in lbs
49049	RING, 1"X-HI QUAD LOCK MATTE	Cap: 15 in lbs Crossbolt: 30 in lbs
49053	RING QUAD LOCK 22 TIP OFF MATTE	Cap: 15 in lbs Crossbolt: 30 in lbs
49055	RING QUAD LOCK 1"MED SLVR	Cap: 15 in lbs Crossbolt: 30 in lbs
49056	RING QUAD LOCK 1"HI SLVR	Cap: 15 in lbs Crossbolt: 30 in lbs
49062	RING, QUAD LOCK 1" HIGH EXT	Cap: 15 in lbs Crossbolt: 30 in lbs
48448	RING,1" EXTRA HI EXT BLACK	Cap: 15 in lbs Crossbolt: 35 in lbs (For 22 TO Crossbolt: 15 in lbs)
48449	RING,1" EXTRA HI EXT MATTE	Cap: 15 in lbs Crossbolt: 35 in lbs (For 22 TO Crossbolt: 15 in lbs)
49030	RING,DET TOP MNT 1"LOW BLACK	Cap: 15 in lbs Crossbolt: 35 in lbs (For 22 TO Crossbolt: 15 in lbs)
49032	RING,DET TOP MT, 1" MED, SS	Cap: 15 in lbs Crossbolt: 35 in lbs (For 22 TO Crossbolt: 15 in lbs)
49033	RING, DET TOP MT, 1" HI SS	Cap: 15 in lbs Crossbolt: 35 in lbs (For 22 TO Crossbolt: 15 in lbs)
49040	RING, DET TP MT,1" LOW, MATT	Cap: 15 in lbs Crossbolt: 35 in lbs (For 22 TO Crossbolt: 15 in lbs)
49041	RING,DET TOP MT,1" MED,MATTE	Cap: 15 in lbs Crossbolt: 35 in lbs (For 22 TO Crossbolt: 15 in lbs)
49042	RING,DET TP MT 1" HIGH, MATT	Cap: 15 in lbs Crossbolt: 35 in lbs (For 22 TO Crossbolt: 15 in lbs)
49043	RING,DET TOP MT,1"EXT HI MAT	Cap: 15 in lbs Crossbolt: 35 in lbs (For 22 TO Crossbolt: 15 in lbs)
49044	RING,DET TP MT, 1" XHI, MATT	Cap: 15 in lbs Crossbolt: 35 in lbs (For 22 TO Crossbolt: 15 in lbs)
49045	RING,DET TOP MT, DUAL EXT MATT	Cap: 15 in lbs Crossbolt: 35 in lbs (For 22 TO Crossbolt: 15 in lbs)

Weaver Recommended Torque Specs

Item ID	Item Name	Torque Specs
Axial Load to Torque of Fastener		
6-48 @ 15 in lbs = 555 lbs 8-40 @ 18 in lbs = 562 lbs 6-48 @ 30 in lbs = 1111 lbs 6-48 @ 35 in lbs = 1296 lbs		
10-32 @ 35 in lbs = 945 lbs 10-32 @ 48 in lbs = 1297 10-32 @ 65 in lbs 1756 lbs		

49050	RING,DET TOP MT, 1" HIGH	Cap: 15 in lbs Crossbolt: 35 in lbs (For 22 TO Crossbolt: 15 in lbs)
49060	RING,DET TOP MT, 1" EXT	Cap: 15 in lbs Crossbolt: 35 in lbs (For 22 TO Crossbolt: 15 in lbs)
49061	RING,DET TOP MT, 1" DUAL EXT	Cap: 15 in lbs Crossbolt: 35 in lbs (For 22 TO Crossbolt: 15 in lbs)
49071	RING,DET TOP MT, 1" MED	Cap: 15 in lbs Crossbolt: 35 in lbs (For 22 TO Crossbolt: 15 in lbs)
49080	RING, DET TOP MT, 1" XHIGH	Cap: 15 in lbs Crossbolt: 35 in lbs (For 22 TO Crossbolt: 15 in lbs)
49090	RING,1" MED,EXT	Cap: 15 in lbs Crossbolt: 35 in lbs (For 22 TO Crossbolt: 15 in lbs)
49091	RING,1" MED EXT,MATTE	Cap: 15 in lbs Crossbolt: 35 in lbs (For 22 TO Crossbolt: 15 in lbs)
49110	RING,DET TOP MT, 30MM HI	Cap: 15 in lbs Crossbolt: 35 in lbs (For 22 TO Crossbolt: 15 in lbs)
49120	RING,DET TOP MT, 30MM HI MATTE	Cap: 15 in lbs Crossbolt: 35 in lbs (For 22 TO Crossbolt: 15 in lbs)
49121	RING,DET TOP MT, 30MM LOW MATT	Cap: 15 in lbs Crossbolt: 35 in lbs (For 22 TO Crossbolt: 15 in lbs)
49143	RING, SURE GRIP W/A 1" MED MATTE	Cap: 15 in lbs Crossbolt: 35 in lbs (For 22 TO Crossbolt: 15 in lbs)
49144	RING, SURE GRIP W/A 1" HI MATTE	Cap: 15 in lbs Crossbolt: 35 in lbs (For 22 TO Crossbolt: 15 in lbs)
49145	RING,SURE GRIP W/A 1" X-HI MATTE	Cap: 15 in lbs Crossbolt: 35 in lbs (For 22 TO Crossbolt: 15 in lbs)
49150	30MM LOW EXT TOP MT MATTE	Cap: 15 in lbs Crossbolt: 35 in lbs (For 22 TO Crossbolt: 15 in lbs)
49152	30MM HI EXT MT MATTE	Cap: 15 in lbs Crossbolt: 35 in lbs (For 22 TO Crossbolt: 15 in lbs)
49155	30MM LOW EXT RINGS SATIN	Cap: 15 in lbs Crossbolt: 35 in lbs (For 22 TO Crossbolt: 15 in lbs)
49156	30MM HI EXT RINGS SATIN	Cap: 15 in lbs Crossbolt: 35 in lbs (For 22 TO Crossbolt: 15 in lbs)
49160	RING,SURE GRIP, 1" MED	Cap: 15 in lbs Crossbolt: 35 in lbs (For 22 TO Crossbolt: 15 in lbs)

Weaver Recommended Torque Specs

Item ID	Item Name	Torque Specs
Axial Load to Torque of Fastener		
6-48 @ 15 in lbs = 555 lbs 8-40 @ 18 in lbs = 562 lbs 6-48 @ 30 in lbs = 1111 lbs 6-48 @ 35 in lbs = 1296 lbs		
10-32 @ 35 in lbs = 945 lbs 10-32 @ 48 in lbs = 1297 10-32 @ 65 in lbs 1756 lbs		

49161	RING,SURE GRIP, 1" HIGH	Cap: 15 in lbs Crossbolt: 35 in lbs (For 22 TO Crossbolt: 15 in lbs)
49162	RING,SURE GRIP, 1" XHI	Cap: 15 in lbs Crossbolt: 35 in lbs (For 22 TO Crossbolt: 15 in lbs)
49163	RING,SURE GRIP, 1" MED, MATTE	Cap: 15 in lbs Crossbolt: 35 in lbs (For 22 TO Crossbolt: 15 in lbs)
49164	RING,SURE GRIP, 1" HIGH, MATTE	Cap: 15 in lbs Crossbolt: 35 in lbs (For 22 TO Crossbolt: 15 in lbs)
49165	RING,SURE GRIP, 1" XHIGH MATTE	Cap: 15 in lbs Crossbolt: 35 in lbs (For 22 TO Crossbolt: 15 in lbs)
49819	RING, PRO-VIEW 1" TIP-OFF	Cap: 15 in lbs Crossbolt: 35 in lbs (For 22 TO Crossbolt: 15 in lbs)

49510	RING,SEE THRU EXT 1" MATTE	Cap: 15 in lbs Crossbolt: 35 in lbs
49512	RING,SEE THRU,1" EXT	Cap: 15 in lbs Crossbolt: 35 in lbs
49513	RING,SEE THRU,1"	Cap: 15 in lbs Crossbolt: 35 in lbs
49515	RING,SEE THRU,1",3/8" GRVD REC	Cap: 15 in lbs Crossbolt: 35 in lbs
49523	RING,SEE THRU, 1" MATTE	Cap: 15 in lbs Crossbolt: 35 in lbs
49711	RING,SEE THRU,RUGER 10/22	Cap: 15 in lbs Crossbolt: 35 in lbs
49713	RING,SEE THRU,1" MARLIN 336	Cap: 15 in lbs Crossbolt: 35 in lbs
49714	RING,SEE THRU,1",REM 7400/7600	Cap: 15 in lbs Crossbolt: 35 in lbs
49715	RING,SEE THRU,1",REM 742/760	Cap: 15 in lbs Crossbolt: 35 in lbs
49734	RING,SEE THRU,RUGER 10/22 SS	Cap: 15 in lbs Crossbolt: 35 in lbs

48349	RING 6HOLE 1"MED MATTE	Cap: 15-20 in lbs Crossbolt: 35-40 in lbs
48350	RING, 6-HOLE 1"HIGH MATTE	Cap: 15-20 in lbs Crossbolt: 35-40 in lbs
48351	RING, 6 HOLE 1"X-HIGH MATTE	Cap: 15-20 in lbs Crossbolt: 35-40 in lbs
48352	RING, 6 HOLE 30MM HIGH MATTE	Cap: 15-20 in lbs Crossbolt: 35-40 in lbs
48353	RING 6HOLE 1" XX-HIGH MATTE	Cap: 15-20 in lbs Crossbolt: 35-40 in lbs
48354	RING 6HOLE 30MM X-HIGH MATTE	Cap: 15-20 in lbs Crossbolt: 35-40 in lbs
48355	RING 6HOLE 30MM LOW MATTE	Cap: 15-20 in lbs Crossbolt: 35-40 in lbs
48356	RING 6HOLE 30MM MED MATTE	Cap: 15-20 in lbs Crossbolt: 35-40 in lbs
48360	RING 4HOLE 1" MED MATTE	Cap: 15-20 in lbs Crossbolt: 35-40 in lbs

Weaver Recommended Torque Specs

Item ID	Item Name	Torque Specs
Axial Load to Torque of Fastener 6-48 @ 15 in lbs = 555 lbs 8-40 @ 18 in lbs = 562 lbs 6-48 @ 30 in lbs = 1111 lbs 6-48 @ 35 in lbs = 1296 lbs 10-32 @ 35 in lbs = 945 lbs 10-32 @ 48 in lbs = 1297 10-32 @ 65 in lbs 1756 lbs		
48361	RING 4HOLE 1" HIGH MATTE	Cap: 15-20 in lbs Crossbolt: 35-40 in lbs
48362	RING 4HOLE 1"X-HIGH MATTE	Cap: 15-20 in lbs Crossbolt: 35-40 in lbs
48363	RING 4HOLE 1" XX-HIGH MATTE	Cap: 15-20 in lbs Crossbolt: 35-40 in lbs
48364	RING 4HOLE 30MM LOW MATTE	Cap: 15-20 in lbs Crossbolt: 35-40 in lbs
48365	RING 4HOLE 30MM MED MATTE	Cap: 15-20 in lbs Crossbolt: 35-40 in lbs
48366	RING 4HOLE 30MM HIGH MATTE	Cap: 15-20 in lbs Crossbolt: 35-40 in lbs
48367	RING 4HOLE 30MM X-HIGH MATTE	Cap: 15-20 in lbs Crossbolt: 35-40 in lbs
99511	Pic 4-Hole Ring 1" Med Matte	Cap: 15 in lbs Crossbolt: 48 in lbs
99512	Pic 4-Hole Ring, 1" Hi Matte	Cap: 15 in lbs Crossbolt: 48 in lbs
99513	Pic, 4-Hole Ring 1" X-Hi Matte	Cap: 15 in lbs Crossbolt: 48 in lbs
99514	Pic 4-Hole Ring, 1" XX-Hi Matte	Cap: 15 in lbs Crossbolt: 48 in lbs
99515	Pic 4-Hole Ring - 30mm Low Matte	Cap: 15 in lbs Crossbolt: 48 in lbs
99516	Pic 4-Hole Ring - 30mm Med Matte	Cap: 15 in lbs Crossbolt: 48 in lbs
99517	Pic 4-Hole Ring - 30mm High Matte	Cap: 15 in lbs Crossbolt: 48 in lbs
99518	Pic 4-Hole Ring - 30mm X-High Matte	Cap: 15 in lbs Crossbolt: 48 in lbs
99682	RING, 34MM TACTICAL LOW	Cap: 25 in lbs Crossbolt: 65 in lbs
99684	RING, 34MM TACTICAL HIGH	Cap: 25 in lbs Crossbolt: 65 in lbs
99686	RING, 34MM TACTICAL EXTRA EXTRA HIGH	Cap: 25 in lbs Crossbolt: 65 in lbs
99688	RING, PICT 6-HOLE 1" MED	Cap: 15 in lbs Crossbolt: 48 in lbs
99689	RING, PICT 6-HOLE 1" HIGH	Cap: 15 in lbs Crossbolt: 48 in lbs
99690	RING, PICT 6-HOLE 1"X-HIGH	Cap: 15 in lbs Crossbolt: 48 in lbs
99691	RING, PICT 6-HOLE 1"XX-HIGH	Cap: 15 in lbs Crossbolt: 48 in lbs
99692	RING, PICT 6-HOLE 30MM LOW	Cap: 15 in lbs Crossbolt: 48 in lbs
99693	RING, PICT 6-HOLE 30MM MED	Cap: 15 in lbs Crossbolt: 48 in lbs
99694	RING, PICT 6-HOLE 30MM HIGH	Cap: 15 in lbs Crossbolt: 48 in lbs
99695	RING, PICT 6-HOLE 30MM X-HIGH	Cap: 15 in lbs Crossbolt: 48 in lbs